



Rely On Ruud

## Packaged AIR CONDITI<sup>°</sup> NERS

### VSNM Series



R-410A  
50Hz



14-gauge G-90 sheet metal base rails allow for easier maneuverability during installation



Pre-paint system rated at 1000 hour salt spray per ASTM B117.



Full-louver coil protection



Easy-to-access control box and internal components



High and low refrigerant pressure gauge ports for easy pressure measurement



Removable, sloped drain pan



Foil-faced insulation to the cabinet



Closed-cell insulation on the base of the unit

RELY ON RUUD.™



# TECHNICAL DATA

VSNM		VSNM-A024TK	VSNM-A036TK	VSNM-A042NK	VSNM-A048NK	VSNM-A048TK	VSNM-A060NK	VSNM-A072NK
Rated Cooling Capacity @AHRI	Btu/hr	21000	31000	36000	40000	42000	52000	63500
EER @AHRI	Btu/W-hr	11.3	11.3	11.1	11.3	11.3	11.3	10.65
Rated Air Flow	CFM	665	1000	1165	1290	1290	1585	2200
Unit Sizes	L (mm)	1499	1499	1499	1499	1499	1499	1499
	W (mm)	838	838	838	838	838	838	838
	H (mm)	740	740	740	943	943	943	943
Weight	kg	148	159	166	186	186	212	217
Refrigerant		R410A						

AHRI Condition: 80°F/67°F On-coil, 95°F ambient

Before proceeding with installation, refer to installation instructions packaged with each model, as well as complying with all Federal, State, Provincial, and Local codes, regulations, and practices.

**RUUD**  
**AIR CONDITIONING**  
**DIVISION**

Dubai Airport Freezone (DAFZA), UAE

