



PACEMAKER®

THE PACEMAKER® GAS WATER HEATER LINE IS ENGINEERED FOR MORE HOT WATER AT A LOW OPERATING COST



Performance:

- FHR: 189 - 511 liters, based on liter capacity
- Recovery rate is 100 to 289 liters at a 50 degree Celsius rise

Features:

- Exclusive Ruudglas® tank lining resists corrosion
- R-Foam® insulation for superior heat retention
- Temperature and pressure relief valve included
- Gasmaster™ burner with precision port alignment for even heat transfer
- Heat saving flue baffle design
- Model specific burners engineered for high MJ/H input
- LP models feature durable stainless steel burners designed specifically for LP gas and Robertshaw® controls
- Side relief valve connection
- Maximum working pressure of 150 PSI (10 BARS)
- Available with Piezo Ignition & Vent Safety Switch

Warranty:

- 6-Year limited for the tank
- 2-Year limited for the parts



DESCRIPTION			FEATURES				DIMENSIONS (SHOWN IN MM)					
TYPE	LTR. CAP.	MODEL NUMBER	MJ/H		RECOVERY IN LTR. @ 50°RISE	FIRST HOUR	TANK	VENT HEIGHT	TANK HEIGHT	VENT SIZE	APPROX SHIP WT. (Kg)	INSULATION THICKNESS
			NAT	LP								
T A L L	114	EX-P 30-6	33.7		122	201	400	1499	1422	76	44	22
	114	EX-P 30-7P		31.6	115	193	400	1499	1422	76	44	22
	151	EX-P 40-7	35.9		130	220	451	1524	1435	76	50	22
	151	EX-P 40-7P		35.9	130	220	451	1524	1435	76	50	22
	189	EX-P 50-2	38		138	257	502	1549	1448	76	65	22
	189	EX-P 50-2P		38	138	257	502	1549	1448	76	65	22
	189	EX-P 50-4	52.7		192	314	502	1549	1448	102	67	22.4
	189	EX-P 50-4P		52.7	192	314	502	1549	1448	102	67	22
	189	EX-P 50-6	63.3		229	360	584	1613	1518	102	81	63
	189	EX-P 50-6P		63.3	229	360	584	1613	1518	102	81	63
	284	EX-P R75	79.1		289	481	667	1638	1537	102	145	54
	284	EX-P R75P		79.1	289	481	667	1638	1537	102	145	54
	379	EX-P 100	79.1		289	511	667	1727	1626	102	159	28
379	EX-P 100P		79.1	289	511	667	1727	1626	102	159	28	
S H O R T	114	EX-P 30S-2	27.4		100	189	451	1238	1149	76	42	22
	114	EX-P 30S-2P		27.4	100	189	451	1238	1149	76	42	22
	151	EX-P 40S-2	29.5		107	250	502	1276	1207	76	46	22
	151	EX-P 40S-2P		29.5	107	250	502	1276	1207	76	46	22

RELY ON RUUD.™